

12  
County Surveyor's Record, Douglas County, Oregon

East Boundary of T .25 S., R 1 W., W.M.,  
as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under  
Contract No. 664 dated May 23, 1896.

CHAINS	
	<p>A Fir, 48 ins. diam., bears S.27*W., 31 lks. dist., marked <math>\frac{1}{2}</math> S B T.</p> <p>This cor., is on a steep hill-side sloping SW.</p> <p style="text-align: right;">Va. 21*30'E.</p>
40.75	Spring, 1 lk. wide, course SW., 75 ft. below creek last noted.
43.75	Creek, 2 lks. wide, course W., begin ascent.
51.55	A Fir, 48 ins. diam., on line. I mark with 2 notches on N and S sides.
62.35	Creek, 1 lk. wide, course W., 50 ft. above creek last noted. Ascend.
65.00	Top of spur, 50 ft. above creek last noted, bears W. Gradually descend to sec. cor., 50 ft. below this spur.
	Diff. bet., measurements of 80.00 chs., by two sets of chainmen is 8 lks., position of middle point By 1st set, 80.04 chs., By 2nd set, 79.96 chs., the mean of which is
80.00	Set a basalt stone, 12x10x8 ins., 8 ins. in the ground for cor. of secs. <sup>13, 18</sup> 19 and 24, marked with 3 notches on N and S edges, from which
	A Fir, 60 ins. diam., bears N.32*E., 72 lks. dist., marked T 25 S R 1 E S 18 B T.,
	A Cedar, 12 ins. diam., bears S.31*E., 33 lks. dist., marked T 25 S R 1 E S 19 B T.,
	A Cedar, 24 ins. diam., bears S.19*W, 12 lks. dist., marked T 25 S R 1 W S 24 B T.,
	A Cedar, 60 ins. diam, bears N.74*W., 44 lks. dist., marked T 25 S R 1 W S 13 B T.
	This cor., is on hillside, sloping S.
	Land, mountainous.
	Soil, 3rd rate.
	Timber, fir, hemlock,, cedar, pine, maple, dog-wood, and alder.
	Dense undergrowth of rhododendron, vinemaple, hemlock, fir, cedar, huckleberry, chinquapin, and sallalberry.