

County Surveyor's Record, Douglas County, Oregon

3487

East boundary of T. 25 S., R 1 W., W.M.

CHAINS	
	<p>Land mountainous and covered with dense undergrowth, 80.00 chs. July 15, 1896</p>
	<p>South, bet. secs. 19 and 24. Descend. Va. 19*E.</p>
15.13	<p>A Fir, 24 ins. diam., on line, I mark with 2 notches on N and S sides. Diff. bet measurements of 40.00 chs., by two sets of chainmen, is 50 lks.. position of middle point By 1st set, 40.25 chs. By 2nd set, 39.75 chs., the mean of which is</p>
40.00	<p>Set a basalt stone, 12x12x10 ins., 8 ins. in the ground for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ on W face, from which A Madrona, 16 ins. diam., bears N.53*E., 12 lks. dist., marked $\frac{1}{2}$ S B T. A Madrona, 10 ins. diam., bears N.62*W., 15 lks. dist., marked $\frac{1}{2}$ S B T. This cor. is on a hillside, sloping SW., about 150 ft. below sec. cor.</p>
40.75	<p>Brink of high bluff on NE side of canyon. Series of impassible bluffs. Set a basalt stone, 24x12x12 ins., 18 ins. in the ground for witness point, marked W P on W face, and raised a mound of stone $3\frac{1}{2}$ ft. base, 2 ft. high, which bears S.45*E., 10 lks. dist., Thence, I offset E., 89 lks., then run South on offset line.</p>
48.34	<p>Offset W., 89 lks., to the meridian line, thence North on true line 2.55 chs.</p>
45.79	<p>Set a basalt stone, 14x12x10 ins., 10 ins. in the ground for witness point, marked W P on W face, and raised a mound of stone 2 ft. high, $3\frac{1}{2}$ ft. base, W of cor. Pits impracticable. This cor. is beside a bluff, 100 ft. high, facing SW. From this point, I run S on true line.</p>
49.15	<p>Foot of descent. Creek, 10 lks. wide, course W., 200 ft. below last witness point.</p>