

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R 1 W., W.M.,
 as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under
 Contract No. 664 dated May 23, 1896.

CHAINS	<p>At this sec. cor., at 9 h., A.M., l.m.t., I set off 21*14'N., on declination arc, and 43*23'N., on lat. arc, and determine a true meridian with the solar.</p>
29.10	<p>South, bet. secs. 25 and 30. Va. 20*E. Creek, 4 lks, wide, course SW, 200 ft. below top of spur, last noted. Descend.</p>
38.25	<p>Top of slight spur, sloping W. Continue descent.</p>
40.00	<p>Diff. bet. measurements of 40.00 chs., by two sets of chainmen, is 2 lks., position of middle point By 1st set, 40.01 chs., By 2nd set, 39.99 chs., the mean of which is Set a basalt stone, 16x14x12 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which A Fir, 10 ins. diam., bears S.85*E., 45 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 36 ins. diam., bears S.60*W., 31 lks. dist., marked $\frac{1}{4}$ S B T. This cor. is on a steep hillside, sloping W. July 16. At this $\frac{1}{4}$ sec. cor., I set off 21*12'N., on decl. arc, and, at apparent noon, observe the sun on the meridian, the resulting lat. is 43*23', which is about 42" greater than the proper lat.</p>
60.65	<p>Creek, 2 lks. wide, course W., 50 ft. below top of spur, last noted.</p>
67.75	<p>Creek, 1 lk. wide, course W., 50 ft. below creek last noted. Diff. bet. measurements of 80.00 chs., by two sets of chainmen, is 8 lks., position of middle point By 1st set, 80.04 chs., By 2nd set, 79.96 chs., the mean of which is</p>