

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R 1 W., W.M.,
as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under
Contract No. 664 dated May 23, 1896.

CHAINS

39.80 Creek, 6 lks. wide, course East.
Diff. bet. measurements of 40.00 chs., by two sets of
chainmen, is 10 lks., position of middle point
By 1st set, 40.05 chs.,
By 2nd set, 39.95 chs., the mean of which is

40.00 Set a basalt stone, 14x12x10 ins. 10 ins. in the ground
for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which
A Fir, 36 ins. diam., bears N.80 $\frac{1}{2}$ *W., 43 lks.
dist., marked $\frac{1}{4}$ S B T.
An Alder, 6 ins. diam., bears N.52*E., 14 lks.
dist, marked $\frac{1}{4}$ S B T.
This cor. is on right bank of creek.
Ascend.

52.40 Creek, 3 lks, wide, course E., 75 ft. above McKinley
Creek. Continue ascent.

59.75 Creek, 2 lks, wide, course E. 125 ft. above McKinley
Creek.
Diff bet. measurements of 80.00 chs., by two sets of
chainmen, is 16 lks., position of middle point
By 1st set, 80.08 chs.
By 2nd set, 79.92 chs., the mean of which is

80.00 Set a basalt stone, 16x12x10 ins., 12 ins. in the
ground for cor of Tps. 25 and 26 S., Rgs 1 E and
1 W., marked with 6 notches on each edge, from which
An alder, 12 ins. diam., bears N.33*E., 47 lks. dist
marked T 25 S R 1 E S 31 B T.
A Fir, 60 ins. diam., bears S.33*E., 72 lks. dist.,
marked T 26 S R 1 E S 6 B T.
A Fir, 12 ins. diam., bears S.10*W., 50 lks. dist.,
marked T 26 S R 1 W S 1 B T.
A Fir, 24 ins. diam., bears N.57*W., 80 lks. dist.,
marked T 25 S R 1 W S 36 B T.
This cor. is on a steep hillside sloping E., 225 ft.
above McKinley Creek.
Land mountainous.
Soil, 3rd rate.