

26

16

County Surveyor's Record, Douglas County, Oregon

South Boundary T. 25 S., R. 1 W., W.M.,  
as surveyed by Hezekiah H. Johnson, U.S. Deputy Surveyor,  
under Contract 721, dated May 1, 1900.

CHAINS	
	I begin at the cor. of Tps. 25 and 26 S R 1 E and 1 W., and run West bet. secs. 1 and 36, Over mountainous land, through heavy timber and dense undergrowth. Ascend 200 ft. to
8.50	Spur slopes SE and trail from Rock Creek to Steamboat Creek, bears NW and SE and ascend gradually along steep rocky south face.
40.00	Set a fir post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 36 on N and S 1 on S faces, from which A Fir, 14 ins. diam., bears S.86*E., 162 lks. dist., marked $\frac{1}{4}$ S 1 B T. A Fir, 10 ins. diam., bears N.87*W., 195 lks., dist., marked $\frac{1}{4}$ S 36 B T., and ascend 50 ft. to
42.00	Spur slopes S and descend 180 ft. to
49.75	Spring branch, 1 lk wide, flows S and ascend 40 ft. to
55.00	Spur slopes S and descend 60 ft. to
60.00	Ravine, course S and ascend 200 ft. to
69.00	Spur slopes S and descend 150 ft. to
77.00	Ravine, course S, and ascend 50 ft. to
80.00	The point for sec. cor. falls on a projecting point of rock in place 18x12x6 ins. above ground. At the exact cor. point, I cut a cross (†) for cor. of secs. 1, 2, 35, and 36 and mark 5 grooves on West, 1 groove on E of cross, from which A point of rock, 3 ft. high, bears N.45*E., 19 lks. dist., marked † - B.O A Fir, 10 ins. diam., bears S.26*E., 87 lks. dist., marked T 26 S R 1 W S 1 B T. A Fir, 18 ins. diam., bears S.85*W., 74 lks. dist., marked T 26 S R 1 W S 2 B T. A Maple, 4 ins. diam., bears N.70*W., 63 lks. dist., marked T 25 S R 1 W S 35 B T  Land, mountainous.