

County Surveyor's Record, Douglas County, Oregon

3505

South Boundary, T. 25 S., R 1 W., W.M.

CHAINS

59.80

Brook, 8 lks. wide, flows S.20\*E., and ascend.

80.00

Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 5, 6, 31, and 32, marked

T 25 S S 32 on NE.

R 1 W S 5 on SE.

T 26 S S 6 on SW and

S 31 on NW. faces, with 5 notches on E and 1 notch on W edges, from which

A Fir, 9 ins. diam., bears N.72\*E., 45 lks. dist., marked T 25 S R 1 W S 32 B T.

A Fir, 9 ins. diam., bears S.73 $\frac{1}{2}$ \*E., 33 lks. dist., marked T 26 R 1 W S 5 B T.

A Fir 11 ins. diam., bears S.1\*W., 29 lks. dist., marked T 26 S R 1 W S 6 B T.

A Fir, 8 ins. diam., bears N.69\*W., 86 lks. dist., marked T 25 S R 1 W S 31 B T.

Land mountainous.

Soil rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, fir, hemlock, maple, and hazel.

Mountainous land, or land covered with heavy timber or dense undergrowth, 80.00 chs.

West bet. secs. 6 and 31.

Over mountainous land through heavy timber and dense undergrowth.

Ascend.

40.00

The point for  $\frac{1}{4}$  sec. cor. falls on a basalt stone in place, 12x12x5 ft. above ground, at the exact cor. point I cut a cross (†) for  $\frac{1}{4}$  sec. cor., and marked  $\frac{1}{4}$  on N. side of cross, from which

A Fir, 22 ins. diam., bears S.32\*W., 18 lks. dist., marked  $\frac{1}{4}$  S 6 B T.

A Fir, 4 ins. diam., bears N.20\*W., 17 lks. dist., marked  $\frac{1}{4}$  S 31 B T.