

53

County Surveyor's Record, Douglas County, Oregon

Subdivisional Lines of T. 25 S., R 1 W., W.M.,
as surveyed by Hezekiah H. Johnson, U.S. Deputy Surveyor,
under Contract No. 721, dated May 1, 1900.

CHAINS	
	At the cor. of secs. 1, 2, 35 & 36 on S. bdy. of Tp. <i>Thence</i> N 1'W bet. secs. 35 and 36.
	Over mountainous land, through scattering timber and dense undergrowth.
	Ascend steep south slope, about 400 ft. to
33.00	Trail on top of spur bears NW and SE and descend about 60 ft. to
37.50	Ravine, course SE., spring, 25 lks. E of line, flows SE and ascend.
40.00	The point for $\frac{1}{4}$ sec. cor. falls on exposed bedrock, on which I cut a cross (+) at the exact cor. point for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ on W side of cross, from which
	A Fir, 36 ins. diam., bears S.88*E., 52 lks. dist., marked $\frac{1}{4}$ S 36 B T.
	A Fir, 28 ins. diam., bears N.88*W., 49 lks. dist., marked $\frac{1}{4}$ S 35 B T.
47.00	Spur slopes SE and descend through heavy green timber, bears NW and SE about 300 ft. to
55.00	Foot of steep descent, thence on NE slope.
60.51	Spring branch, 1 lk. wide, flows NE .
66.00	Brow of hill bears E and W and descend 300 ft. to
80.00	A Hemlock, 5 ins. diam., for cor. of secs. 25, 26, 35 and 36, I mark
	T 25 S S 25 on NE.
	R 1 W S 36 on SE.
	S 35 on SW and
	S 26 on NW sides, with 1 notch on N and E sides, from which
	A Hemlock, 8 ins. diam., bears N.89*E., 3 lks. dist., marked T 25 S R 1 W S 25 B T.
	A Hemlock, 12 ins. diam., bears S.51*E., 22 lks. dist., marked T 25 S R 1 W S 36 B T.
	A Hemlock, 6 ins. diam., bears S.80*W., 41 lks. dist., marked T 25 S R 1 W S 35 B T.
	A Chinquapin, 8 ins. diam., bears N.40*W., 14 lks. dist., marked T 25 S R 1 W S 26 B T.