

37
County Surveyor's Record, Douglas County, Oregon

3511

Subdivisions T. 25 S., R 1 W., W.M.

CHAINS	
51.00	Summit of ridge bears N and S and descend steep rocky hill 600 ft. to
73.51	Canton Creek, 175 lks. wide, flows SE and ascend 75 ft. to
80.36	The cor of secs. 23, 24, 25 and 26. Land mountainous. Soil rocky, 2nd to 4th rate Timber, fir and pine. Undergrowth, fir, hemlock, rhododendron and chinquapán. Mountainous land, or land covered with heavy timber or dense undergrowth, 80.36 chs.
	Aug. 2, 1900
	N.1'W., bet. secs 23 and 24. Over mountainous land, through heavy timber and dense undergrowth. Descend 75 ft. to
2.00	Canton Creek, 74 lks. wide, flows S.60°E and enter level bottom.
24.00	Descend 20 ft. to
24.75	Canton Creek, 80 lks. wide, flows SW.
31.25	Canton Creek flows S.40°E., and ascend steep, rocky, SW slope, 200 ft. to
40.00	Set a basalt stone, 18x9x8 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which A Fir, 20 ins. diam., bears N.53°E., 49 lks. dist., marked $\frac{1}{4}$ S 24 BT. A Fir, 6 ins. diam., bears S.14°W., 25 lks. dist., marked $\frac{1}{4}$ S 23 B T., and continue ascent 200 ft. to
51.00	Spur slopes W and descend 40 ft. to
53.00	Ravine, course W and ascend steep rocky hill 250 ft. to
66.50	Spur slopes W and descend 150 ft. to
76.85	Spring branch, 2 lks. wide, flows W and ascend 75 ft. to
80.00	Set a basalt stone, 22x12x7 ins., 16 ins. in the ground for cor. of secs. 13, 14, 23 and 24, marked with