

33

County Surveyor's Record, Douglas County, Oregon

3527

Subdivisions T. 25 S., R1 W., W.M.

CHAINS	
	<p>Undergrowth, vinemaple, firm hemlock and alder.</p> <p>Mountainous land, or land covered with heavy timber or dense undergrowth, 80.32 chs.</p> <p style="text-align: right;">Aug. 10th, 1900</p>
	<p>N.2'W., bet. secs. 10 and 11.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Descend 75 ft. to</p>
7.55	Spring Branch, 2 lks. wide, flows E.
9.00	Spring branch, 2 lks. wide, flows SE., and ascend 75 ft. to.
13.00	Spur slopes E and descend 150 ft. to
34.85	Stream, 15 lks. wide, flows E and ascend.
40.00	Set a cedar post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 10 on W., S 11 on E., faces, from which
	A Cedar, 8 ins. diam., bears N.72*W., 28 lks. dist., marked $\frac{1}{4}$ S 10 B T.
	A Hemlock, 18 ins. diam., bears S.70*E., 25 lks. dist., marked $\frac{1}{4}$ S 11 B T.
50.00	Spur, 250 ft. above stream slopes E and descend 100 ft. to
53.00	Ravine, course E and ascend 60 ft. to
55.00	Spur slopes E and descend 150 ft. to
59.50	Brook, 10 lks. wide flows S.80*E., and ascend 100 ft. to
70.50	Spur slopes E and descend 40 ft. to
74.09	Spring branch, 1 lk. wide, flows SE and ascend 75 ft. to
79.30	Spur slopes SE and descend.
80.00	Set a basalt stone, 20x15x15 ins., 15 ins. in the ground for cor. of secs. 2, 3, 10, and 11, marked with 5 notches on S and 2 notches on E edges, from which
	A Fir, 10 ins. diam., bears N.43*E., 45 lks. dist., marked T 25 S R 1 W S 2 B T.