

56

County Surveyor's Record, Douglas County, Oregon

Subdivisions T. 25 S., R 1 W., W.M.

CHAINS	
	<p>Timber, fir, hemlock, cedar, pine and alder.</p> <p>Undergrowth, chinquapin, rhododendron, arbutus, dogwood, alder and hazel.</p> <p>Mountainous land, or land covered with heavy timber or dense undergrowth, 80.39 chs.</p> <p style="text-align: right;">Aug. 12th, 1900</p>
	<p>N.2*W., bet. secs. 33 and 34.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Descend 150 ft. to</p>
11.51	Spring branch, 3 lks. wide, flows NE and ascend 40 ft. to
15.00	Spur slopes E and descend 100 ft. to
20.93	Brook, 10 lks. wide, flows SE., and ascend.
40.00	<p>Set a basalt stone 15x10x7 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which</p> <p style="padding-left: 40px;">A Fir, 24 ins. diam., bears N.45*E., 65 lks. dist., marked $\frac{1}{4}$ S 34 B T.</p> <p style="padding-left: 40px;">A Maple, 6 ins. diam., bears N.40*W., 50 lks. dist., marked $\frac{1}{4}$ S 33 B T.</p>
49.00	Spur slopes W., about 400 ft. above stream and descend 100 ft. to
55.50	Ravine, course W., and descend 200 ft. to
65.50	Spur slopes W and descend 150 ft. to
74.80	Spring branch, 2 lks. wide, flows SW and ascend 150 ft. to
80.00	<p>The point for sec. cor., falls on bare bed rock, I cut a cross (+) at the exact cor. point for the cor. of secs. 27, 28, 33 and 34, marked with 1 groove S and 3 grooves E of cross, from which</p> <p style="padding-left: 40px;">A Fir, 24 ins. diam., bears N.74*E., 33 lks. dist., marked T 25 S R 1 W S 27 B T.</p> <p style="padding-left: 40px;">An Arbutus, 6 ins. diam., bears S.55*E., 46 lks. dist., marked T 25 S R 1 W S 34 B T.</p> <p style="padding-left: 40px;">A point of rock bears S.65*W., 39 lks. dist., marked + B O.</p>