

65  
County Surveyor's Record, Douglas County, Oregon

3539

Subdivisions T. 25 S., R 1 W., W.M.

CHAINS

66.50

Spur slopes E and descend 150 Ft. to

80.00

Set a cedar post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 3, 4, 9, and 10, marked

T 25 S S 3 on NE.

R 1 W S 10 on SE.

S 9 on SW and

S 4 on NW faces with 5 notches on S and 3 notches on E edges, from which

A Dogwood, 7 ins. diam., bears N.20\*E., 21 lks. dist., marked T 25 S R 1 W S 3 B T.

A Hemlock, 7 ins. diam., bears S.28\*E., 21 lks. dist., marked T 25 S R 1 W S 10 B T.

A Dogwood, 6 ins. diam., bears S.20\*W., 9 lks. dist., marked T 25 S R 1 W S 9 B T.

A Chinquapin, 7 ins. diam., bears N.84\*W., 20 lks. dist., marked T 25 S R 1 W S 4 B T.

Land mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, hemlock, pine, and cedar.

Undergrowth, hemlock, fir, maple, willow, chinquapin, and dogwood.

Mountainous land, or land covered with heavy timber or dense undergrowth, 80.00 chs.

40.00

S.89\*56'E., on a random line bet. secs. 3 and 10.

Set a temp.  $\frac{1}{4}$  sec. cor.

80.20

Intersect N and S line, 27 lks. S of the cor. of secs. 2, 3, 10, and 11.

Thence I run

S.89\*52'W., on a true line bet. secs. 3 and 10.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend.

40.10

A Dogwood, 5 ins. diam., for  $\frac{1}{4}$  sec. cor., I mark  $\frac{1}{4}$  S 3 on N and S 10 on S sides, from which

A Chinquapin, 5 ins. diam., bears S.20\*W., 8 lks.