

County Surveyor's Record, Douglas County, Oregon

Subdivisions T. 25 S., R 1 W., W.M.

CHAINS

21.30	Spring branch, 4 lks. wide, flows N and ascend.
40.08	Set a basalt stone, 16x9x8 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which A Fir, 5 ins. diam., bears N.5*E., 15 lks. dist., marked $\frac{1}{4}$ S 20 B T. A Hemlock, 4 ins. diam., bears S.24*E., 6 lks. dist., marked $\frac{1}{4}$ S 29 B T.
44.00	Spur slopes N about 300 ft. above spring branch and descend 200 ft. to
59.00	Spring branch, 4 lks. wide, flows N and ascend 250 ft. to
75.50	Spur slopes N.20*E., thence along steep N slope to
80.16	The cor. of secs. 19, 20, 29 and 30. Land mountainous. Soil, clay loam, 2nd rate. Timber, fir, hemlock, cedar and pine. Undergrowth, vinemaple, fir, hemlock, chinquapin, arbutus and dogwood. Mountainous land, or land covered with heavy timber or dense undergrowth, 80.16 chs.
	Aug. 27th, 1900
	West on a true line bet. secs. 19 and 30. Over mountainous land, through heavy timber and dense undergrowth. Descend 200 ft. to
9.95	Spring branch, 5 lks. wide, flows N and ascend 150 ft. to
16.50	Spur slopes N and descend 100 ft. to
23.25	Ravine, course N and ascend.
40.00	Set a basalt stone, 17x8x8 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which A Fir, 6 ins. diam., bears N.18*W., 44 lks. dist., marked $\frac{1}{4}$ S 19 B T. A Fir, 5 ins. diam., bears S.32*W., 12 lks. dist., marked $\frac{1}{4}$ S 30 B T.,