

97
County Surveyor's Record, Douglas County, Oregon

3571

Retracement of the North boundary of T. 26 S., R 1 W.,
as surveyed by Fred Mensch, Deputy Surveyor, under Contract No.
797, dated April 19, 1910.

CHAINS

At the cor of secs. 1, 2, 35 and 36, on S bdy.

T 25 S R 1 W.

This cor. is partially obliterated, no trace being found of the cor. of the NW bearing tree. The other bearing trees and the bearing rock are found. I re-establish the cor. in its original position as the cor. of secs. 35 and 36, T 25 S R 1 W, only as follows:

Point for cor. of secs. 35 and 36 falls on a basalt rock in place, 18x12x6 ins. above ground on which I cut a cross (+) at exact corner point, with 1 notch E and 5 notches W of cross, from which

A point of rock, 3 ft. high, bears N.45°E., 19 lks. dist., marked P O 36.

A Maple, 6 ins. diam., bears N.76½°W., 73 lks. dist., marked T 25 S R 1 W S 35 P T.

I obliterate marks on former bearing trees referring to T 26 S.

Thence I run

W on S bdy., sec. 35, T 25 S, R 1 W.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along S. Slope.

23.00 Creek, 1 lk. wide, course S.

Ascend E slope.

40.10 The ¼ sec. cor., which is a post almost destroyed by fire, marked and witnessed as described by the surveyor general.

I re-establish the cor. in its original position as the ¼ sec. cor. on S bdy., sec. 35, T 25 S R 1 W, only, as follows:

Set a basalt stone, 15x10x10 ins., 10 ins. in the ground for ¼ sec. cor. on S bdy., sec. 35, marked ¼ on N face, from which