

## Retracement of the North Boundary of T. 26 S., R 1 W.

CHAINS

A Fir, 24 ins. diam., bears N.35\*E., 146 lks.  
dist., marked S 35 B T.

A Fir, 18 ins. diam., bears N.70\*W., 22 lks.  
dist., marked S 35 B T.

I obliterate marks on former bearing tree referring  
to sec. 2.

The course of this line is West and the distance is  
40.10 chs.

West on S bdy. sec. 35, T 25 S R 1 W.

Ascend E slope.

1.00 Ridge bears N and S.

Descend W. slope.

18.40 Ravine, course S.

Ascend SE slope.

30.00 Ridge point descending S.

Descend W slope.

40.10 The cor. of secs. 2, 3, 34 and 35, which is a basalt  
stone, 5x10x5 ins. above ground, firmly set, marked  
and witnessed as described by the surveyor general.  
I re-establish this cor. as the cor. of secs. 34 and  
35, T 25 S R 1 W, only, by obliterating marks on  
bearing trees referring to T 26 S.

The course of this line is West and the distance is  
40.10 chs.

Land mountainous.

Soil, stony, 4th rate.

Timber, fir, undergrowth, hazel, vinemapple and fir.

July 24, 1910

At the cor. of secs. 34 and 35, T 25 S R 1 W.

Thence I run

West on S bdy., sec. 34, T 25 S R 1 W.

Over mountainous land, heavily timbered and covered with  
dense undergrowth.

Descend W. slope.