

County Surveyor's Record, ¹⁰ Douglas County, Oregon

Retracement of the North Boundary of T. 26 S., R 1 W.

CHAINS
40.20

The cor. of secs. 5, 6, 31 and 32, which is a fir post, 4 ins. sq., 12 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except the NE bearing tree, which cannot be found.

I re-establish this cor. in its original position as the cor. of secs. 31 and 32, T 25 S R 1 W., only, as follows:

Post above described, already set, from which

A Fir, 12 ins. diam., bears N.84*E., 27 lks. dist., marked T 25 S R 1 W S 32 B T.

A Fir, 10 ins. diam., bears N.69*W., 86 lks. dist., marked T 25 S R 1 W S 31 B T.

I obliterate marks on bearing trees referring to T 26 S.

The course of this line is West and the distance is 40.20 chs.

Land mountainous.

Soil, stony, 4th rate.

Timber, fir.

Undergrowth, vinemaple, hazel, fir.

West on S bdy., sec. 31, T 25 S R 1 W.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Ascend E slope.

39.81

The $\frac{1}{4}$ sec. cor. on rock, 12x12x5 ft., marked and witnessed as described by the surveyor general.

I re-establish this cor. in its original position as the $\frac{1}{4}$ sec. cor. on S bdy., sec. 31, T 25 S R 1 W., only, as follows:

Rock above described, from which

A Fir, 10 ins. diam., bears N.31 $\frac{1}{2}$ *E., 66 lks. dist., marked $\frac{1}{4}$ S 31 B T.

A Fir, 4 ins. diam., bears N.20*W., 17 lks. dist., marked $\frac{1}{4}$ S 31 B T.