

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 2 W., W. M.

CHAINS	sec. 36 and at,
39.25	The $\frac{1}{4}$ sec. cor. between secs. 1 and 36, bears North 60 lks. dist.
78.50	The cor. of secs. 1, 2, 35 & 36 bears North 141 lks. dist.
117.71	The $\frac{1}{4}$ sec. cor. between secs. 2 and 35 bears North 169 lks. dist.
156.98	The cor. of secs. 2, 3, 34 and 35 bears North 195 lks. dist.
196.19	The $\frac{1}{4}$ sec. cor. between secs. 3 and 34 bears North 233 lks. dist.
235.50	The cor. of secs. 3, 4, 33 and 34 bears North 270 lks. dist.
274.75	The $\frac{1}{4}$ sec. cor. between secs. 4 and 33 bears North 285 lks. dist.
313.90	The cor. of secs. 4, 5, 32 and 33 bears North 302 lks. dist.
353.24	The $\frac{1}{4}$ sec. cor. between secs. 5 and 32 bears N 319 lks. dist.
392.49	The cor. of secs. 5, 6, 31 and 32 bears North 335 lks. dist.
431.68	The $\frac{1}{4}$ sec. cor. between secs. 6 and 31 bears North 353 lks. dist.
470.01	Intersect the W boundary of T. 323 lks. S of the $\frac{1}{4}$ sec. cor. between secs. 31 and 36, which is an alder stake 3 ins. sq., firmly set, marked and witnessed as described by the Surveyor General.
	It becomes necessary, therefore, to establish a sectional correction line on which to base the subdivisions of this Township.

and Extension Lines
Subdivisions of T. 25 S., R. 2 W., W. M.

At the cor. of secs. 25, 30, 31 and 36 on the East boundary of Tp.
Thence I run,