

County Surveyor's Record, Douglas County, Oregon

33

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	An arbutus, 24 ins. diam., bears N.38°W., 12 lks. dist., marked $\frac{1}{4}$ S 11 B T.
40.55	Spring branch, 2 lks. wide, flows SW.
56.42	Spring branch, 1 lk. wide, flows W.
60.00	Spur, slopes W about 700 ft. above Rock Creek, thence along W slope of mountain descending.
76.00	Spring branch, 2 lks. wide, flows SW and ascend 50 ft. to
80.00	Set a basalt stone 18 x 8 x 6 ins., 12 ins. in the ground for cor. of secs. 1, 2, 11 and 12 marked with 5 notches on S and 1 notch on E edges, from which, A fir, 48 ins. diam., bears N.30°E., 9 lks. dist., marked T 25 S R 2 W S 1 B T. A cedar, 6 ins. diam., bears S.68°E., 50 lks. dist., marked T 25 S R 2 W S 12 B T. A fir, 14 ins. diam., bears S.19 $\frac{1}{2}$ °W., 15 lks. dist., marked T 25 S R 2 W S 11 B T. A fir, 36 ins. diam., bears N.24°W., 14 lks. dist., marked T 25 S R 2 W S 2 B T.
	Land mountainous and level. Soil clay loam, 2nd rate. Timber fir, hemlock, cedar, pine and arbutus. Undergrowth vine maple, fir, hemlock, chinquapin and arbutus. Mountainous land or land covered with heavy timber or dense undergrowth. 80 chs.
	June 30th, 1900.
	N.89°58'E on a random line between secs. 1 and 12.
40.00	Set a temp. $\frac{1}{4}$ sec. cor.
80.30	Intersect the E boundary of Tp. 5 lks. N of the cor. of secs. 1, 6, 7 and 12. Thence I run, West on a true line between secs. 1 and 12. Over mountainous land, through heavy timber and dense undergrowth. Along S slope of mountain.