

39

County Surveyor's Record, Douglas County, Oregon

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS 17.00	Enter flat bears E and W.
31.00	Descend 100 ft. to
37.00	Ravine, course NW and ascend.
37.34	Set a basalt stone 16 x 12 x 6 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face, from which A fir, 10 ins. diam., bears N.62*30'E., 80 lks. dist., marked $\frac{1}{4}$ S 34 B T. A fir, 8 ins. diam., bears S.52*W., 50 lks. dist., marked $\frac{1}{4}$ S 33 B T.
40.00	Spur, slopes NW 50 ft. above ravine and descend 200 ft. to
53.34	Spring branch, 2 lks. wide, flows W. Thence over rolling ground.
58.26	Trail to Rock Creek bears NW and SE.
58.41	Spring branch, 3 lks. wide, flows S.80*W and enter old burn bears E and W.
70.18	Spring branch, 3 lks. wide, flows S.70*W., and ascend 60 ft. to
77.34	The cor. of sec. 27, 28, 33 and 34. Land mountainous. Soil clay loam, 2nd rate. Timber fir, hemlock and pine. Undergrowth arbutus, chinquapin, alder, willow, fir and hemlock. <p style="text-align: right;">July 8th, 1900.</p>
	At cor. of secs. 27, 28, 33 and 34. Thence I run, N.2*W between secs. 27 and 28. Over rolling ground, through dense undergrowth.
15.00	Top of hill bears E and W and enter heavy timber and descend.
35.50	Spring branch, 1 lk. wide, flows NW.
40.00	Set a cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 28 on W and S 27 on E faces, from which