

## Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	
	At the cor. of secs. 9, 10, 15 and 16. Thence I run, N. 2° W between secs. 9 and 10. Over mountainous land, through heavy timber and dense undergrowth. Ascend along W. slope.
24.75	Spring branch, 1 lk. wide in ravine 20 ft. deep, flows W.
25.50	Spring branch, 1 lk. wide, flows SW.
39.25	Spring branch, 1 lk. wide, flows SE.
40.00	Set a basalt stone 16 x 10 x 8 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face, from which A yew, 8 ins. diam., bears S. 56° E., 45 lks. dist., marked $\frac{1}{4}$ S 10 B T. A yew, 8 ins. diam., bears N. 75° W., 20 lks. dist., marked $\frac{1}{4}$ S 9 B T.
42.03	A fir, 36 ins. diam., on line, I mark with 2 notches on N and S sides.
54.00	Summit of ridge bears NW and SE about 500 ft. above sec. cor., thence along steep rocky E slope.
80.00	Set a basalt stone 16 x 10 x 6 ins., 11 ins. in the ground for cor. of secs. 3, 4, 9 and 10 marked with 5 notches on S and 3 notches on E edges, from which A yew, 8 ins. diam., bears N. 30° E., 96 lks. dist., marked T 25 S R 2 W S 3 B T. A hemlock, 24 ins. diam., bears S. 25° E., 30 lks. dist., marked T 25 S R 2 W S 10 B T. A yew, 8 ins. diam., bears S. 66° W., 104 lks. dist., marked T 25 S R 2 W S 9 B T. A cedar, 12 ins. diam., bears N. 45° W., 24 lks. dist., marked T 25 S R 2 W S 4 B T.  Land mountainous. Soil rocky, 3rd and 4th rate. Timber fir, hemlock, cedar, pine and yew.