

County Surveyor's Record, Douglas County, Oregon

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	<p>A pine, 4 ins. diam., bears N.31*E., 28 lks. dist., marked T 25 S R 2 W S 28 B T.</p> <p>A maple, 4 ins. diam., bears S.15*E., 27 lks. dist., marked T 25 S R 2 W S 33 B T.</p> <p>A fir, 48 ins. diam., bears S.25*W., 30 lks. dist., marked T 25 S R 2 W S 32 B T.</p> <p>An alder, 5 ins. diam., bears N.11*W., 8 lks. dist., marked T 25 S R 2 W S 29 B T.</p>
	<p>Land mountainous and rolling.</p> <p>Soil clay loam, rocky, 3rd rate.</p> <p>Timber fir, hemlock, cedar and pine.</p> <p>Undergrowth arbutus, spicewood, rhododendron, willow, hazel and hemlock.</p> <p>Mountainous land or land covered with heavy timber or dense undergrowth. 80 chs.</p>
40.00	<p>S.3'E on a random line between secs. 32 and 33.</p> <p>Set a temp. <math>\frac{1}{4}</math> sec. cor.</p>
77.03	<p>Intersect the S boundary of the Tp. 600 lks. W of the cor. of secs. 4, 5, 32 and 33, which is a post 4 ins. sq., marked and witnessed as described by the Surveyor General.</p> <p>At the point of intersection I set a basalt stone 15 x 11 x 6 ins., 10 ins. in the ground for closing cor. of secs. 32 and 33 marked C C with 4 notches on E and 2 notches on W edges, from which</p> <p>A hemlock, 10 ins. diam., bears N.20*E., 42 lks. dist., marked C C T 25 S R 2 W S 33 B T.</p> <p>A hemlock, 4 ins. diam., bears N.51*W., 65 lks. dist., marked C C T 25 S R 2 W S 32 B T.</p> <p>Thence I run,</p> <p>N.3'W on a true line between secs. 32 and 33.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p>