

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	Thence over rolling ground.
39.87½	Set a basalt stone 18 x 10 x 8 ins., 12 ins. in the ground for ¼ sec. cor. marked ¼ on N face, from which A fir, 30 ins. diam., bears S.21*E., 45 lks. dist., marked ¼ S 28 B T. A maple, 10 ins. diam., bears N.15*E., 59 lks. dist., marked ¼ S 21 B T.
59.50	Enter swampy ground bears N and S.
62.00	Leave swamp bears N and S.
70.00	Leave rolling ground bears NW and SE and descend 70 ft. to
79.51	Brook, 12 lks. wide, flows NW.
79.75	The cor. of secs. 20, 21, 28 and 29. Land mountainous and rolling. Soil clay loam, 2nd rate. Timber fir, hemlock, cedar, pine and maple. Undergrowth arbutus, hemlock, maple, willow and hazel. Mountainous land or land covered with heavy timber or dense undergrowth. 79.75 chs.
	N.3'W between secs. 20 and 21. Through heavy timber and dense undergrowth.
0.17	Brook, 12 lks. wide, flows W and ascend 60 ft. to
10.00	Spur, slopes W and descend 80 ft. to
18.00	Enter creek bottom bears NE and SW.
20.50	Channel of Rock Creek, 20 lks. wide, flows SW.
27.00	Main channel of Rock Creek, 75 lks. wide, flows SW.
31.00	Enter clearing bears NE and SE. J. H. Shoups house bears N.64*W about 10 chs. dist. Barn bears N.74*W about 7 chs. dist.
37.05	Wagon road bears NE and SW. Leave clearing bears NE and SW and ascend mountain.
40.00	Set a hemlock post 3 ft. long, 3 ins. sq., 24 ins. in the ground for ¼ sec. cor. marked ¼ S 20 on W and S 21 on E faces, from which