

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	<p>Connecting line. 6.00 chs.</p> <p style="text-align: right;">July 20th, 1900.</p>
	<p>At the cor. of secs. 19, 20, 29 and 30.</p>
	<p>Thence I run,</p>
	<p>N.4°W between secs. 19 and 20.</p>
	<p>Over mountainous land, through heavy timber and dense undergrowth.</p>
	<p>Ascend 160 ft. to</p>
22.00	<p>Spur, slopes SE and descend.</p>
40.00	<p>Set a basalt stone 18 x 7 x 7 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face, from which</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S.75°E., 26 lks. dist., marked $\frac{1}{4}$ S-20 B T.</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S.49°W., 40 lks. dist., marked $\frac{1}{4}$ S-19 B T.</p>
41.84	<p>Spring branch, 2 lks. wide, flows SE about 100 ft. below spur and ascend.</p>
43.10	<p>Pine, 72 ins. diam., on line I mark with 2 notches on N and S sides.</p>
44.34	<p>A fir, 72 ins. diam., on line I mark with 2 notches on N and S sides.</p>
60.00	<p>Spur, slopes E about 250 ft. above spring branch and descend 60 ft. to</p>
65.40	<p>Spring branch, 1 lk. wide, flows E and ascend 50 ft. to</p>
70.25	<p>Spur, slopes E and descend 40 ft. to</p>
72.56	<p>Spring branch, 1 lk. wide flows E. Thence along steep rocky E slope.</p>
80.00	<p>A point on edge of precipice 25 ft. high, drops E. Set temp. object and measure West 20 lks. onto safe ground and set a basalt stone 16 x 10 x 8 ins., 11 ins. in the ground for witness cor. to cor. of secs. 17, 18, 19 and 20, marked W C with 3 notches on S and 5 notches on E edges, from which</p>