

County Surveyor's Record, Douglas County, Oregon

-67-

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	
	<p>A fir, 36 ins., diam., bears N.25*E., 8 lks. dist., marked W C T 25 S R 2 W S 17 B T.</p> <p>A fir, 36 ins., diam., bears S.45*E., 19 lks. dist., marked W C T 25 S R 2 W S 20 B T.</p> <p>An arbutus, 10 ins. diam., bears S.43*W., 38 lks. dist., marked W C T 25 S R 2 W S 19 B T.</p> <p>A hemlock, 5 ins. diam., bears N.53*W., 38 lks. dist., marked W C T 25 S R 2 W S 18 B T.</p> <p>Land mountainous.</p> <p>Soil clay loam, 2nd and 3rd rate.</p> <p>Timber fir, hemlock, cedar and pine.</p> <p>Undergrowth hemlock, fir, maple and arbutus.</p> <p>Mountainous land or land covered with heavy timber or dense undergrowth. 80 chs.</p>
40.00	<p>N.89*54'E on a random line between secs, 17 and 20.</p> <p>Set a temp. $\frac{1}{4}$ sec. cor.</p>
80.20	<p>Intersect N and S line at the cor. of secs. 16, 17, 20 and 21.</p> <p>Thence I run,</p> <p>S.89*54'W on a true line between secs. 17 and 20.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Descend 30 ft. to</p>
1.00	<p>Spring branch, 5 lks. wide, flows SE and ascend.</p>
22.00	<p>A pine, 60 in. diam., on line I mark with 2 notches on E and W sides.</p>
23.50	<p>Spur, slopes S and descend along SW face.</p>
40.10	<p>Set a basalt stone 16 x 10 x 7 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which</p> <p>A maple, 14 ins. diam., bears N.69*W., 14 lks. dist., marked $\frac{1}{4}$ S 17 B T.</p> <p>A fir, 21 ins. diam., bears S.68*W., 11 lks. dist., marked $\frac{1}{4}$ S 20 B T.</p>
58.40	<p>Shoup Creek, 12 lks. wide, flows SE about 180 ft. below spur, and ascend 250 ft. to</p>