

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	
65.61	Spring branch; 3 lks. wide, flows SE and ascend.
76.00	Spring branch, 1 lk. wide, flows S.10*W.
80.00	Set a basalt stone 16 x 9 x 9 ins., 11 ins. in the ground for cor. of secs. 7, 8, 17 and 18 marked with 4 notches on S and 5 notches on E edges, from which A hemlock, 26 ins. diam., bears N.18*E., 27 lks. dist., marked T 25 S R 2 W S 8 B T. A hemlock, 10 ins. diam., bears S.65*E., 20 lks. dist., marked T 25 S R 2 W S 17 B T. A fir, 40 ins. diam., bears S.51*W., 79 lks. dist., marked T 25 S R 2 W S 18 B T. A fir, 40 ins. diam., bears N.64*W., 56 lks. dist., marked T 25 S R 2 W S 7 B T. Land mountainous. Soil clay loam, rocky, 2nd and 3rd rate. Timber fir, hemlock, cedar and pine. Undergrowth hemlock, fir, yew and vine maple. Mountainous land or land covered with heavy timber or dense undergrowth. 80 chs.
40.00	N.89*54'E on a random line between secs. 8 and 17. Set a temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N and S line 16 lks. N of the cor. of secs. 8, 9, 16 and 17. Thence I run, N.89*59'W on a true line between secs. 8 and 17. Over mountainous land, through heavy timber and dense undergrowth. Ascend.
4.32	A pine, 80 ins. diam., on line, I mark with 2 notches on E and W sides.
21.00	Spur, slopes NE about 300 ft. above sec. cor. and descend 200 ft. to
36.90	Spring branch, 1 lk. wide, flows NE and ascend.