

County Surveyor's Record, Douglas County, Oregon
-73-

Subdivisional and Exterior Lines of T. 25 S., R. 2 W., W. M.

CHAINS	
40.05	<p>Set a cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 8 on N and S 17 on S faces, from which</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears S.6*W., 20 lks. dist., marked $\frac{1}{4}$ S 17 B T.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N.35*W., 21 lks. dist., marked $\frac{1}{4}$ S 8 B T.</p>
74.00	Top of ascent bears N and S about 400 ft. above spring branch, thence over rolling S slope.
80.00	Spring branch, flows S.
80.20	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land mountainous.</p> <p>Soil clay loam, 2nd rate.</p> <p>Timber fir, hemlock, cedar and pine.</p> <p>Undergrowth hemlock, fir, cedar and vine maple.</p> <p>Mountainous land or land covered with heavy timber or dense undergrowth. 80.20 chs.</p>
	<p>West between secs. 7 and 18.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Along S slope.</p>
5.83	A fir, 40 ins. diam., on line, I mark with 2 notches on E and W sides.
19.54	Spring branch, 1 lk. wide, flows S.
33.11	Brook, 6 lks. wide, flows S and ascend.
40.00	<p>Set a basalt stone 16 x 8 x 8 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face, from which</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears N.35*W., 47 lks. dist., marked $\frac{1}{4}$ S 7 B T.</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S.16*W., 62 lks. dist., marked $\frac{1}{4}$ S 18 B T.</p>
64.46	Intersect W boundary of Tp. 6.99 chs. S of the cor. of secs. 7, 12, 13 and 18, which is a post 4 ins. sq., marked and witnessed as described by the Surveyor General.