

County Surveyor's Record, Douglas County, Oregon

/3

Subdivisions of Fractional T. 25 S., R. 7 W.

CHAINS		
	West. On True Line between Sections 27 and 34.	
40.15	Set $\frac{1}{4}$ Section Post, from which A B. Oak, 18 ins. diam., bears N.89*W., 693 lks. A B. Oak, 15 ins. diam., bears South, 367 lks.	+150
62.00	Summit of ridge, course N.&S.	+500
74.25	A Branch, 3 lks. wide, course SE.	-100
80.30	To Corner. Land about the same as last mile.	
	North. Between Sections 27 & 28.	
6.90	A Branch, 5 lks. wide, course SE. Va. 18*30'E.	-100
25.50	Offset N.30*W. 3.50 chs. Thence N.30*E., 3.50 chs. to avoid a high ridge of rocks.	+400
31.56	Intersect line again near summit of mountain, C. NE. & SW.	+100
40.00	Set $\frac{1}{4}$ Section Post, from which A Fir, 24 ins. diam., bears N.64*W., 12 lks. A Fir, 15 ins. diam., bears N.22*E., 22 lks.	-50
75.10	A Branch, 5 lks. wide, course East.	-500
80.00	Set Post Corner of Secs. 21, 22, 27 & 28, from which A Fir, 12 ins. diam., bears S.46*W., 23 lks. A Fir, 15 ins. diam., bears S.22*E., 33 lks. A Fir, 20 ins. diam., bears N.52*W., 30 lks. A Fir, 12 ins. diam., bears N.20*E., 35 lks. Land mountainous. Timber, principally fir. Soil, 3d rate.	+40
	East. On Random between Sections 22 & 27.	
40.00	Set temporary $\frac{1}{4}$ Section Post. Va. 18*30'E.	
79.90	Intersect N. & S. Line 50 lks. South of Corner. S.89*39'W. On True Line between Secs. 22 and 27.	
9.60	Leave John Churchill's field, course N. & S.	Level
18.60	Intersect left bank of Umpqua River, and set Meander Post from which	Level