

County Surveyor's Record, Douglas County, Oregon

19

West Boundary of T. 25 S., R. 7 W.,
as surveyed by Dennis Hathorn, Deputy Surveyor,
under Contract No. 73, dated June 8, 1857.

CHAINS	South, on West Boundary Sec. 6.	Va. 19*10'E.	
6.25	Branch, 1 lk. wide, course W.		-25
23.50	Branch, 1 lk. wide, course NE.		-50
29.25	Creek, 25 lks. wide, course NNW..		-50
31.00	Leave same, course NE.		
36.00	Same, course NW.		
38.90	Same, course NE.		
40.00	Set qr. sec. post and built stone mound in edge of same creek, from which A Maple, 12 ins. diam., bears N.2*W., 322 lks. A Myrtle, 20 ins. diam., bears N.40'E. 25 lks.		
62.50	Summit of sharp ridge, course E.&W.		+400
80.00	Intersect left bank of Umpqua River and set post corner Secs. 6, 7, 1 & 12, from which A Fir, 12 ins. diam., bears N.42*E., 87 lks. A Fir, 9 ins. diam., bears N.7*E., 60 lks. A Laurel, 10 ins. diam., bears N.15*W., 65 lks. An Oak, 12 ins. diam., bears N.45*W., 44 lks. No bearing trees convenient south of corner. Land, hilly. Timber, fir, cedar. Undergrowth, maple, hazel and pine. Soil, 3d rate.		-500
	South, on West Boundary Sec. 7.	Va. 19* E.	
	From a point on opposite bank of river 29 chs. East run, S. 9.14 chs.; thence West 29 chs. to line. Course of River is NE.		
9.14	Mark a Willow 6 ins. in diam. for Meander Cor. right bank of river, from which A Willow, 10 ins. diam., bears N.80*E., 4 lks. A Fir, 12 ins. diam., bears S.80*W., 9 lks.		
40.00	Set $\frac{1}{2}$ Sec. post, from which		+20