

County Surveyor's Record, Douglas County, Oregon

38

Subdivisions of T. 25 S., R. 7 W., W. M.

CHAINS 45.00	A Spring branch, course NW.	+150
63.00	A Spring branch, course NW.	+150
77.50	A creek, 5 lks. wide, course N.	-200
80.96	To sec. cor.	
	Land, mountainous, 3rd and 2nd rates.	
	Timber, same as preceding mile, 1st rate.	
	South, on a true line between secs. 28 and 29.	
	Va. 19°E.	
26.90	A Fir, 30 ins. diam.	
40.00	Set Laurel post for $\frac{1}{4}$ sec. cor. from which	+400
	A Fir, 10 ins. diam., bears N.1 $\frac{1}{2}$ °E., 79 lks. dist.	
	A Cedar, 60 ins. diam., bears N.55°W., 72 lks. dist.	
74.00	Top of ridge, course W.	+600
80.00	Set fir post for cor. to secs. 28, 29, 32 and 33 from	+400
	which	
	A Cedar, 30 ins. diam., bears N.12°E., 12 lks. dist.	
	A Laurel, 14 ins. diam., bears S.39°E., 11 lks. dist.	
	A Laurel, 4 ins. diam., bears S.65 $\frac{1}{2}$ °W., 11 lks. dist.	
	A Cedar, 30 ins. diam., bears N.18°W., 45 lks. dist.	
	Timber, generally dead. Underbrush and briars very	
	thick. Pea Vine in places.	
	June 9, 1874.	
	Begin at the established cor. to secs. 31 and 32 on	
	S. boundary, run N. on true line.	
	Va. 18 $\frac{1}{2}$ °E.	
2.00	Top of ridge, course W.	+50
12.00	A creek, 2 lks. wide, course W.	-300
35.00	Top of ridge, course E and W.	
40.00	Set fir post for $\frac{1}{4}$ sec. cor. from which	
	A Hemlock, 30 ins. diam., bears S.67°E., 35 lks. dist.	
	A Fir, 10 ins. diam., bears S.34°W., 31 lks. dist.	