

## County Surveyor's Record, Douglas County, Oregon

52

## Subdivisions of T. 25, S., R. 7 W., W. M.

CHAINS

A Fir, 12 ins. diam., bears S.5\*W., 79 lks. dist.  
marked T 25 S R 7 W B T.

A Laurel, 18 ins. diam., bears N.20\*W., 46 lks. dist.  
marks overgrown.

This being out of required limits with the reported  
length of the S. bdy. of sec. 33, and the S. bdy. of  
sec. 21 and being satisfied of the accuracy of my  
measurement, I proceed to ascertain cause.

I go to the cor. of secs. 3, 4, 33 and 34 and thence run  
West, on blank line along S bdy. of sec. 33.

42.25  $\frac{1}{4}$  sec. cor. bears 6 lks. S.

84.60 The cor. of secs. 4, 5, 32 and 33.

This distance placing the S bdy. of sec. 33 out of  
prescribed limits with my line by excess of length  
in order to further investigate, I test the align-  
ment of the W bdy. of sec. 33 and find it practically  
correct. I now go to the cor. of secs. 3, 4, 33 and  
34 and run thence

North, on blank line between secs. 33 and 34.

40.06  $\frac{1}{4}$  sec. bears W. 80 lks. dist.

80.03 The cor. of secs. 27, 28, 33 and 34 bears W. 156 lks.  
dist.

The true bearing, therefore, of the E bdy. of sec. 33  
is therefore N.1\*07\*W.

From the cor. of secs. 27, 28, 33 and 34, I run  
North, on blank line between secs. 27 and 28.

39.98  $\frac{1}{4}$  sec. cor. bears W. 5 lks. dist.

79.97 The cor. of secs. 21, 22 27 and 28.

Thence I run

N.89\*21\*W. on a blank line between secs. 21 and 28.