

54

Subdivisions of T. 25 S., R. 7 W., W. M.

CHAINS

To survey and mark sectional correction line between secs. 9 and 16, 8 and 17, and 7 and 18, I begin at the cor. of secs. 9, 10, 15 and 16, which is a yew post still standing and in good condition. Witness trees all in position, marks overgrown on alder and willow. Marking plain on the firs, 1c: T 25 S R 7 W S 16 B T, and T 25 S R 7 W S 9 B T.

Oct. 31, 1896.

At this cor. I set off $14^{\circ}28'S$ on the decl. arc and at 11 hrs 44 m A m, 1, m, t, observe the sun on the meridian, resulting lat. $43^{\circ}25'N$. a trifle less than the proper lat.

Thence I run

West, on a true line between secs. 9 and 16 to establish a sectional correction line.

Ascend from cor.

- 17.50 Summit of ridge 50 ft. above cor. bears N and S. Descend.
- 32.00 A small branch, 50 ft. below summit, course N. Ascend.
- 40.00 Set a fir post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face from which
 A fir, 6 ins. diam., bears $N.45^{\circ}W.$, 40 lks. dist. marked $\frac{1}{4}$ S B T.
 A Fir, 12 ins. diam., bears $S.13^{\circ}E.$, 34 lks. dist. marked $\frac{1}{4}$ S B T.
- 59.00 Summit of ridge bears N and S, 80 ft. above creek. Descend.
- 61.00 Dry gulch, course N. 50 ft. deep. Ascend.
- (69.00) Summit of ridge, 100 ft above gulch bears N and S.
- 80.00 Set a yew post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for cor. of secs. 8, 9, 16 and 17, marked T 25 S S 9 on NE., R 7 W S 16 on SE., S 17 on SW., and S 8 on NW faces with 4 notches on S and E edges from which

SEE 1896
G.L.O. PLAT