

County Surveyor's Record, Douglas County, Oregon

57

subdivisions of T 25 S., R. 7 W., W. M.

CHAINS

A fir post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for closing cor. of secs. 7 and 8 marked C C T 25 S R 7 W on N., S 8 on E and S 7 on W. faces with 5 grooves on E and 4 grooves on S. faces from which

A Maple, 18 ins. diam., bears N.85*W., 24 lks. dist. marked C C T 25 S R 7 W S 7 B T.

A dogwood,, 6 ins. diam., bears N.28*E., 65 lks. dist. marked C C T 25 S R 7 W S 8 B T.

Obliterate marking on the cor. for secs. 7, 8, 17 and 18, referring to these sections.

Thence I run

N.0*2'W. on true line between secs. 7 and 8 (making my random line a true line).

Descend steep mountain, slope from cor.

26.70 To witness cor. between secs. 7 and 8 on S bank of Umpqua River, 200 ft. below sec. cor.

Land, mountainous.

Soil, 4th rate.

Timber, Fir, Maple and Cedar.

Undergrowth, arrowwood, hazel and Myrtle.

Mountainous land, or land covered with dense undergrowth 26.70 chs.

Nov. 3, 1896.

At the cor. of secs. 16, 17, 20 and 21, I set off 15*42' on the dec. arc. and at 11 hs. 44M a, m, 1, m, t, observe the sun on the mer. resulting lat. 43*24'N.

From the cor. of secs. 16, 17, 20 and 21 which is an oak post firmly set in the ground, marked and witnessed as described by the Surveyor General, I run

N.0*1'W. on a random line between secs. 16 and 17.