

County Surveyor's Record, Douglas County, Oregon

Retracement of East Bdy. T. 25 S., R. 9 W.

CHAINS

78.79 Fall 94 lks. West of the cor. of secs. 1, 6, 7, and 12, (which is a sandstone, firmly set, marked and witnessed as described by the Surveyor General, and which I now change to refer to secs. 1 and 12, T. 25 S., R. 9 W., only)

The true course of this line, from the $\frac{1}{4}$ sec. cor., is N. 0°47'E., and the length is 39.69 chs.

This sec. line is well cut out and blazed and has good corners

July 20, 1911

At the cor. of secs. 1 and 12

Thence I run

North, retracing the East bdy. sec. 1

40.00 Fall 20 lks. East of the $\frac{1}{4}$ sec. cor. bet. secs. 1 and 6 (which is a sandstone (instead of a hemlock post) firmly set, marked $\frac{1}{4}$ on W. face, and witnessed as described by the Surveyor General, and which I now change to refer to Sec. 1, T. 25 S., R. 9 W., only).

The true course of this line is N.0°17'W., and the length is 40.00 chs.

74.85 Fall 45 lks. East of the closing cor. for Tps. 25S., Rs. 8 and 9 W., which is a post, marked and witnessed as described by the Surveyor General.

The true course of this line, from the $\frac{1}{4}$ sec. cor. to the closing cor. is N.0°25'W. and the length is 34.85 chs.

NOTE:-

This closing cor. is not set on the S. Bdy. of Sec. 36, T 24 S., R. 9 W. (found and retraced by me, July 20, 1911, and hereinbefore noted), as reported in field notes returned by Chas. L. Campbell, U. S. Deputy Surveyor, under his contract No. 747, dated May 5, 1902, but is some distance south of same. I continue my measurements North, from old closing cor. of T. 25 S., Rs. 8 and 9 W. along W. Bdy. sec. 6, T. 25 S., R. 8 W.

90.45 Creek, $\frac{1}{2}$ lk. wide course East

Ascend steep ridge, in heavy timber and dense brush

95.00 Descend over rimrocks, 300 ft. high bears E. and W.