

County Surveyor's Record, Douglas County, Oregon

CHAINS

From the cor. of secs. 9, 10, 15 and 16, I resurvey the South and East boundaries of sec. 16, according to the old notes of said lines, the same conditions existing as to absence of lines and corners as heretofore described.

Thence I proceed to the cor. of secs. 32 and 33, on the South bdy. of township, and retrace the old line northerly and find evidence of the old corners of secs. 28, 29, 32 and 33 and 20, 21, 28 and 29, which I reestablish to refer to secs. 28, 33, and 21 and 28, only, and continue line to an intersection with the cor. of secs. 16 and 21, previously reestablished. Thence I proceed N. 0° 2' W., and at 80 chs. establish cor. for secs. 9, and 16, and at 160 chs. cor. for secs. 4 and 9, and continue to an intersection with the South bdy. of T. 24 S., R. 8 W., where I set a closing cor. for secs. 4 and 5.

I also retrace the south bdys. of secs. 31 and 32 and the east bdy. of T. 25 S., R. 9 W., where I find a hiatus bet. Ts. 24 and 25 S., R. 9 W., as hereinafter noted.

This method of resurveying and reestablishing these old lines, was furnished the U. S. Surveyor General's Office at Portland and by them transmitted to the Hon. Commissioner of the General Land Office, at Washington, and approved by him in letter "E" 199117- A.V.R. dated Feb. 19, 1912.

Survey by:

Retracement and Resurvey of Subdivisional Section Lines T. 25 S., R. 8 W. As surveyed by Morris Wygant, Compassman for Zachariah M. Derrick U. S. Deputy Surveyor, Under Contract No. 779, dated Feb. 7, 1908