

49

Retracement and Resurvey of Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

T 26 S 5 on SW., and S 32 on NW. faces; with 4 notches on E. and 2 notches on W. edge from which

A fir, 40 ins. diam., bears N.60°E. 23 lks. dist.

marked T 25 S R 8 W S 33 B T

A fir, 40 ins. diam., bears S.85°E. 81 lks. dist.

marked T 26 S R 8 W S 4 B T

A fir, 45 ins. diam., bears S.15°W. 10 lks. dist.

marked T 26 S R 8 W S 5 B T

A hemlock, 40 ins. diam., bears N.45°W. 32 lks. dist.

marked T 25 S R 8 W S 32 B T

Thence I run

North on retracement bet. secs. 32 and 33, following faint traces of old line, in heavy timber and dense undergrowth, exceptionally difficult to survey.

39.95 Intersect the $\frac{1}{4}$ sec. cor. bet. secs. 32 and 33 which is a post, firmly set, marked and witnessed as described by the Surveyor General

The true course of this line is North, and the distance is 39.95 chs.

83.00 The cor. for secs. 28, 29, 32 and 33, bears E. 64 lks. dist. This cor. was badly decayed; otherwise marked and witnessed as described by the Surveyor General.

I now change this cor. to refer to secs. 28 and 33 only, as follows: At the exact point, where old cor. stood, I set a new cedar post, 3 ft. long, 4 ins. sq. 24 ins. in the ground, for cor. of secs. 28 and 33, marked T 25 S S 28 on NE., R 8 W S 33 on SE., with 1 notch on S. and 3 notches on N. edges; from which

A fir, 24 ins. diam., bears N.70°E. 47 lks. dist.

marked T 25 S R 8 W S 28 B T

A fir, 29 ins. diam., bears S.80°E. 64 lks. dist.

marked T 25 S R 8 W S 33 B T

The true course of this line, from the $\frac{1}{4}$ sec. cor. to the cor. of secs. 28 and 33, is N.0°51'E., and the length is 43.06 chs.