

Extension Survey
Subdivisional Lines of T. 25 S., R. 8 W.

CHAINS

// Same Contract. //

At the cor. of secs. 9, 10, 15 and 16, previously described.

Thence I run

N. 0° 1' W. bet. secs. 9 and 10

Descend through scattering timber and dense undergrowth exceptionally difficult to survey

1.91 Creek, 2 lks. wide, course W.

Ascend through burnt timber.

7.00 Bottom of steep, rocky ridge

24.00 Edge, burned timber, bears E. And W.

27.25 Top of rocky ridge, bears E. and W.

Descend almost impassable slope, through dense undergrowth

34.50 Creek 1 lk. wide course NE.

40.00 Set a dogwood post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 9 on W. and 10 on E. faces; from which

A fir, 36 ins. diam., bears N.45°E. 35 lks. dist.
marked $\frac{1}{4}$ S 10 B T

A fir, 42 ins. diam., bears N. 53°W. 37 lks. dist.
marked $\frac{1}{4}$ S. 9 B T

Descend through dense undergrowth and scattering burnt timber.

50.80 Creek 2 lks. wide course NW.

59.30 Creek 2 lks. wide course NW.

72.00 Bottom of ridge, 900 ft. descent.

73.00 Wolf Creek 15 lks. wide course N.70°E.

Ascend ridge, in green timber

80.00 Set yew post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for cor. of secs. 3, 4, 9 and 10 marked T 25 S S 3 on NE., R 8 W S 10 on SE., S 9 on SW. and S 4 on NW. faces; with 5 notches on S. and 3 notches on E. edges; from which

A fir, 18 ins. diam., bears N.75°E. 65 lks. dist.
marked T 25 S R 8 W S 3 B T

A fir, 18 ins. diam., bears S.5°E. 51 lks. dist.