

County Surveyor's Record, Douglas County, Oregon

62
Extension Survey of
Subdivisional Lines of T. 25 S., R. 8 W.

CHAINS	
	Descend steep slope, through dense timber and underbrush, exceptionally difficult to survey
3.50	Creek, 2 lks. wide, course SE. Ascend
8.00	Top of ridge bears E. and W. Descend
24.25	Creek, 8 lks. wide, course E. Ascend
36.84	Set a fir limb post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. for sec. 5 only marked $\frac{1}{4}$ S 5 on W. face; from which A laurel, 14 ins. diam., bears S.30*W. 34 lks. dist. marked $\frac{1}{4}$ S 5 B T A fir, 30 ins. diam., bears N.50*W. 19 lks. dist. marked $\frac{1}{4}$ S 5 B T
38.00	Top of rock ledge, bears E. and W.
40.00	Set a fir post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. for sec. 4 only marked $\frac{1}{4}$ S 4 on E. face; from which A fir, 22 ins. diam., bears S. 56*10'E. 71 lks. dist. marked $\frac{1}{4}$ S 4 B T A fir, 20 ins. diam., bears N.89*50'E. 61 lks. dist. marked $\frac{1}{4}$ S 4 B T
47.00	Top of Gase Knife ridge, bears E. and W. 1000 ft. above sec. cor. trail, bears E. and W. Descend
61.50	Spur of ridge, slopes W.
65.00	Creek, 8 lks. wide, course W. Ascend
69.00	Top of spur, bears E. and W. Descend
81.10	Creek 2 lks. wide, course NE. Ascend
83.72	Intersect the S. Bdy. of Tp. 24 S., R. 8 W., 3.01 chs. N.89*21'W. from the cor. of secs. 32 and 33, previously described.