

County Surveyor's Record, Douglas County, Oregon

71
 Extension Survey of
 Subdivisional Lines of T. 25 S., R. 8 W.

CHAINS	
	Descending steep slope, through dense timber and underbrush, exceptionally difficult to survey.
1.80	Dry canyon, course N. Ascend
4.50	Top of ridge, bears N. and S.; descend
5.75	Dry canyon, course NW.; ascend.
9.50	Top of ridge, bears NW. and SE. descend
14.20	Dry canyon, course NW. ascend
17.00	Top of ridge, bears NW. and SE. descend
22.50	Dry canyon, course NW. ascend
25.00	Top of ridge, bears NW. and SE. descend
26.65	Dry canyon, course SW. ascend
31.00	Top of ridge, bears NE. and SW.; descend
40.00	Set a chinquapin post, 3 ft. long, 4 ins. sq. 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 19 on N. and 30 on S. face; from which A fir, 30 ins. diam., bears N.87*36'E., 72 lks. dist. marked $\frac{1}{4}$ S 19 B T. A fir, 24 ins. diam., bears S.3*20'E. 72 lks. dist. marked $\frac{1}{4}$ S 30 B T.
47.75	Creek 1 lk wide course NW.
66.00	Creek 2 lks. wide course NW. ascend
79.75	Intersect the E. bdy. of T. 25 S., R 9 W. 6.29 chs. N. of the cor. of secs. 24 and 25. At point of intersection, I set a vine maple post, 3 ft. long, 4 ins. sq. 24 ins. in the ground for closing cor. of secs. 19 and 30 marked C C T 25 S R. 8 W on E., S 19 on N. and S 30 on S. faces; with 2 grooves on S. and 4 grooves on N. faces; from which A fir, 24 ins. diam., bears N.40*30'E. 87 lks. dist. marked T 25 S R 8 W S 19 B T. A fir, 30 ins. diam., bears S.57*20'E. 53 lks. dist. marked T 25 S R 8 W S 30 B T.
	Land, mountainous
	Soil; 2nd and 3rd rate