

County Surveyor's Record, Douglas County, Oregon

76
 Extension Survey of
 Subdivisions of T. 25 S., R. 8 W.

CHAINS

At the cor. of secs. 17, 18, 19 and 20

Thence I run

N.0°2'W. bet. secs. 17 and 18

Descend through heavy timber and dense undergrowth,
 exceptionally difficult to survey.

5.25 Creek, 1 lk. wide, course NE.

11.70 Top of ridge, bears E. and W.

Descend through heavy timber and dense undergrowth

40.00 Set hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 18 on W. and 17
 on E. face, from whichA hemlock, 24 ins. diam., bears N.38°E. 34 lks. dist.
 marked $\frac{1}{4}$ S 17 B TA maple, 12 ins. diam., bears N.45°W. 55 lks. dist.
 marked $\frac{1}{4}$ S 18 B T

43.65 Creek, 1 lk. wide, course NE.

60.00 Dry canyon, course NE.; ascend

64.00 Top of ridge, bears NE. and SW.; descend

72.50 Top of ridge, bears E. and W.

80.00 I set a fir post, 3 ft. long, 4 ins. sq. 24 ins. in the
 ground, for cor. of secs. 7, 8, 17 and 18, marked T 25
 S S 8 on NE., R 8 W S 17 on SE., S 18 on SW., and S 7
 on NW. face; with 4 notches on S. and 5 notches on E.
 edges; from whichA fir, 14 ins. diam., bears N.2°20'E. 21 lks. dist.
 marked T 25 S R 8 W S 8 B TA fir, 10 ins. diam., bears S.45°E. 51 lks. dist.
 marked T 25 S R 8 W S 17 B TA maple, 10 ins. diam., bears S.70°30'W. 14 lks.
 dist., marked T 25 S R 8 W S 18 B TA fir, 24 ins. diam., bears N.43°30'W. 14 lks. dist.
 marked T 25 S R 8 W S 7 B T

Land, mountainous

Soil; 2nd and 3rd rate

Timber, heavy fir, hemlock, cedar and maple