

## County Surveyor's Record, Douglas County, Oregon

22

Extension Survey of  
Subdivisional Lines of T. 25 S., R. 8 W.

CHAINS

S R 8 W on E., S 6 on N. and S 7 on S. face; with 5 grooves on S. and 1 groove on N. face; from which

A hemlock, 30 ins. diam., bears N.20\*40'E. 67 lks. dist. marked T 25 S R 8 W S 6 B T

A cedar, 20 ins. diam., bears S.83\*E. 55 lks. dist. marked T 25 S R 8 W S 7 B T

Land, mountainous

Soil, 2nd and 3rd rate

Timber, heavy fir, hemlock, cedar and alder

Mountainous land, covered with heavy timber and dense undergrowth, and exceptionally difficult to survey, 80.26 chs.

August 11, 1911

At the cor. of secs. 5, 6, 7 and 8

Thence I run

N.0\*02'W. bet. secs. 5 and 6

Ascend steep slope, through dense timber and underbrush, exceptionally difficult to survey.

12.00 Top of ridge, bears E. and W.; descend

40.00 Set fir post, 3 ft. long 4 ins. sq. 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S 6 on W. and 5 on E. face; from which

A fir, 6 ins. diam., bears N.50\*15'E. 10 lks. dist. marked  $\frac{1}{4}$  S 5 B T

A fir, 6 ins. diam., bears N.3\*W. 28 lks. dist. marked  $\frac{1}{4}$  S 6 B T

57.65 Creek, 5 lks. wide, course NW.; ascend

64.70 Edge of plateau, over level plateau, through dense timber and underbrush

87.47 Intersect the S. bdy. of T. 24 S., R 8 W. 3.45 chs. S. 89\*56'W. of the cor. of secs. 31 and 32, previously described

At point of intersection, set a fir limb post, 3 ft. long, 4 ins. sq. 24 ins. in the ground, for closing cor. of secs. 5 and 6 marked C C T 25 S R 8 W on S.,