

North Boundary of T. 26 S. R. 9 W., W. M.
As Surveyed by John W. Meldrum U. S. Deputy Surveyor, under
his contract No. 662, dated May 21, 1896.

CHAINS

West, on a random line along the N. Bdy. of T. 26 S., R. 9 W., setting $\frac{1}{4}$ sec. and sec. cors. at intervals of 40.00 chains, and at 456.11 chs. intersect the E. bdy. of T. 25 S., R. 10 W., 383 lks. N. of the cor. of T. 25 and 26 S., Rs. 9 and 10 W., which is a Myrtle post 5 ins. sq. firmly set in the ground, marked and witnessed as described by the Surveyor General.

This falling being beyond the limit prescribed for connecting the proper township, corners by a right line between them; at the point of intersection of my random line with the E. bdy of T. 25 S., R. 10 W., 383 lks. N. of the cor. of T. 25 and 26 S., R. 9 and 10 W. above described.

I set a hemlock post 3 ft. long, 4 ins. sq. 24 ins. in the ground for closing cor. of T. 25 and 26 S., R. 9 W., marked

T 25 S S 31 on N,

C C R 9 W on E and

T 26 S S 6 on S faces with 6 grooves on N., S. and E. faces; from which,

A hemlock, 22 ins. diam., bears N.62°E, 22 lks. dist., marked T 25 S R 9 W S 31 B T.

A hemlock, 22 ins. diam., bears S.24°E, 25 lks. dist., marked T. 26 S R 9 W S 6 B T.

June 9, 1897

Note, the survey of the random line on N. bdy. of T. 26 S., R. 9 W. began in June 7, and completed on June 9, is not dated at the close of each days work. It may be proper to note here at the part of the work accomplished each day was as follows:

June 7, 1897; N. Bdy., of secs, 1 and 2.