

5  
County Surveyor's Record, Douglas County, Oregon

North Boundary of T. 26 S., R. 9 W., W. M.

CHAINS

with dense undergrowth, 80.00 chs.

June 10, 1897

June 11,

East on a true line bet. Secs. 4 and 33, descend along SE. slope

Va. 19°20'E.

9.25	Foot of hill enter bottom bears NE. and SW.	-100
9.50	Creeks 40 lks, wide comes from E. runs SW.	
20.75	Leaves creek, 40 lks. wide, comes from SE, runs W.	
27.40	Creek 40 lks. wide runs SW.	
28.00	Leaves bottom and ascend along NW slope	
35.20	Spring branch 1 lk. wide, runs N.	+300
40.00	Set myrtle post 3 ft. long 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face; from which A maple 24 ins. diam. bears S. 40°E. 54 lks. dist. marked $\frac{1}{4}$ S., B T. A hemlock 30 ins. diam. bears N.27°W. 30 lks. dist. marked, $\frac{1}{4}$ S., B T.	+100
43.75	Spring branch 2 lks. wide runs N.	-150
48.25	Top of Spur course N.	+200
51.75	Spring branch 2 lks. wide runs N.	-200
57.00	Top of Spur course N.	+250
59.25	Spring branch 2 lks. wide, runs NW.	-75
70.75	Top of ridge bears NW and SE.	+400
80.00	Set fir post 3 ft. long, 4 ins. sq. 24 ins. in the ground for cor. of Secs. 3, 4, 33 and 34, marked, T. 25 S., S, 34 on NE, R. 9 W., S. 3 on SE, T. 26 S. S4 on SW and S. 33 on NW. faces with 3 notches on E. and W. edges, from which, A cedar 18 ins. diam. bears N.67°E. 72 lks. dist. marked T. 25 S., R. 9 W., S. 34, B T. A fir 24 ins. diam. bears S.66°E. 56 lks. dist. marked T. 26 S., R. 9 W., S. 3, B. T.	-150