

Subdivisions of T. 25 S., R. 9 W., W. M.,  
As surveyed by Charles L. Campbell, Deputy Surveyor,  
Under Contract No. 747, Dated May 5 1902

CHAINS	<p>West, on the S. Bdy. of Sec. 36, at 39.90 chs. intersect the <math>\frac{1}{4}</math> Sec. cor., at 80.03 chs., intersect the cor. of secs. 1, 2, 35 &amp; 36 on the S. Bdy. of the T., consequently the S. Bdy. of sec. 36 bears West. Therefore the bearings are as stated by the surveyor general, and my chaining practically agrees with the field notes of the original survey.</p> <p>I commence at the cor., of secs., 1, 2, 35, &amp; 36, on the S. Bdy of the T. which is a post, 4 ins. Sq., 12 ins. above the ground, marked and witnessed as described by surveyor general.</p> <p>Thence I run N.0°01'W. bet., secs. 35 &amp; 36.</p> <p>Ascend S. slope of mountain through scattering timber and some undergrowth.</p> <p>33.00 More gradual ascent.</p> <p>35.25 Summit of mountain, divide bet. Bottom Creek and Coos River, 500 ft. above Sec., cor. bears S80°W., N.80°E. descend gradually N. slope into Bottom Creek Basin.</p> <p>36.75 Steeper descent.</p> <p>40.00 Set a sandstone, 28x15x6 ins., 21 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> on the W. face, from which;</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N.67<math>\frac{1}{2}</math>°E., 65 lks. dist., marked <math>\frac{1}{4}</math> S 36 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.8<math>\frac{1}{2}</math>°W., 24 lks. dist., marked <math>\frac{1}{4}</math> S 35 B T.</p> <p>42.50 Enter heavy timber, bears E. and W.</p> <p>53.25 Ravine, 25 ft. deep, course N.60°W.</p> <p style="padding-left: 40px;">Thence descending along steep W. slope of ridge.</p> <p>78.25 Ridge point, 500 ft. below summit of divide, bears N.10°W., and S.10°E., descend along steep E. slope.</p> <p>80.00 Marked A hemlock, 10 ins. diam., for cor. of secs. 25, 26, 35 &amp; 36, marked T 25 S S 25 on the NE, R 9 W S 36 on SE, S 35 on SW and S 26 on the NW. faces; with 1 notch on the S. and E. edges; from which,</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N.73<math>\frac{1}{2}</math>°E., 42 lks. dist., marked T 25 S R 9 W S 25 B T.</p>
--------	---