

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 9 W.

CHAINS

Thence I run on a true line.

N.0°01'W. bet. secs. 1 and 2.

Ascend S. slope of mountain through heavy timber and scattering undergrowth.

4.00 Summit of Umpqua--Coos divide, 1500 ft. above Bottom Creek, bears N.60°W. and S.60°E.

Descend N. slope.

30.75 Spring branch, 4 lks. wide in ravine 100 ft. deep, course N.30°W.

40.00 Set a sandstone, 24x10x5 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face; from which,
A fir, 70 ins. diam., bears S.9 $\frac{1}{2}$ °W., 57 lks. dist., marked $\frac{1}{4}$ S 1 B T.
A fir, 30 ins. diam., bears S.30 $\frac{1}{2}$ °W., 28 lks. dist., marked $\frac{1}{4}$ S 2 B T.

40.60 Spring branch, 1 lk. wide in ravine 20 ft. deep, course N.60°W.

48.00 Creek, 10 lks. wide, in ravine 50 ft. deep, course N.20°E.

Ascend along W. bank.

49.00 Descend into creek.

51.50 Same creek, 10 lks. wide, course N.30°W.

Thence over bottom land.

59.25 Leave bottom, bears N.30°W., S.30°E. and ascend along W. slope.

67.25 Descend into creek.

75.00 Intersect N. Bdy. of the T. 23.48 chs. W. of the cor. of secs. 35 and 36 on the S. Bdy. of T 24 S R 9 W. which is a post 5 ins. sq., 1 ft. above ground, marked and witnessed as described by the surveyor general.
I destroy all marks on old cor. pertaining to the survey S. At point of intersection.

75.00 Set a sandstone, 24x10x5 ins., 18 ins. in the ground, for closing cor. of secs. 1 & 2, marked C C. on the S. with 1 groove on the E. and 5 grooves on the W. faces; from which,