

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 25 S., R. 9 W.

CHAINS	
	<p>A fir, 48 ins. diam., bears S.10°E., 59 lks. dist., marked T 25 S R 9 W S 1 B T.</p> <p>A hemlock, 24 ins. diam., bears S.60°W., 16 lks. dist., marked T 25 S R 9 W S 2 B T.</p> <p>Land, mountainous.</p> <p>Soil, sandy loam; 1st. and 3rd. rate.</p> <p>Timber, fir, hemlock and cedar.</p> <p>Undergrowth, sallow, huckleberry and vine maple.</p> <p>Mountainous or heavily timbered lands. 75.00 chs.</p> <p style="text-align: right;">October 16, 1902</p>
	<p>Thence I run N.0°02'W. bet. secs 34 and 35.</p> <p>Ascend S. slope of mountain, through scattering timber and dense undergrowth.</p>
34.00	<p>Summit of divide bet. Bottom Creek and Coos River, 500 Ft. above sec. cor., bears E. and W.</p> <p>Descend N. slope of mountain into Bottom Creek.</p>
40.00	<p>Set a sandstone, 28x15x8 ins., 21 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> on the W. face; from which,</p> <p style="padding-left: 40px;">A fir, 38 ins., diam., bears N.39-3/4°E., 250 lks. dist., marked <math>\frac{1}{4}</math> S 35 B T.</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.40<math>\frac{1}{2}</math>°W., 198 lks. dist. marked <math>\frac{1}{4}</math> S 34 B T.</p>
43.00	<p>Enter scattering undergrowth, bears E. and W.</p>
47.00	<p>Leave scattering timber, and enter heavy fir timber, bears E. and W.</p>
70.75	<p>Ravine 100 ft. deep, course N.80°W.</p> <p>Ascend gradually along steep W. slope.</p>
76.50	<p>Ridge point, 200 ft. above foot of ravine, descends toward the NW.</p> <p>Descend along N. slope of mountain.</p>
80.00	<p>Set a sandstone, 18x12x8 ins., 12 ins. in the ground for cor. of secs. 26, 27, 34 and 35, marked with 1 notch on S. and 2 notches on the E. edges; from which,</p>