

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T 25 S., R. 9 W. W. M.,

CHAINS

- 40.00 Marked a hemlock, 8 ins. diam., for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ sec. 10 on the W. face and S. 11 on the E. faces; from which,
- A hemlock, 16 ins. diam bears S.29*E., 11 lks. dist. marked $\frac{1}{4}$ S B T.
- A fir, 8 ins. diam., bears N.10*W., 8 lks. dist., marked $\frac{1}{4}$ S B T.
- 47.25 Bald stony ridge, bears N.10*W. and S.10*E.
Descend steep N. slope into fall Creek.
- 66.50 Branch of Fall Creek, 10 lks. wide, a roaring torrent, course S.80*W., in canyon 500 ft. deep.
Ascend over rolling ground.
- 68.25 Foot of Perpendicular Bluffs, 60 ft. high, course E. & W.
Over level ground.
- 78.75 Branch of Fall Creek, 8 lks. wide, course S.60*W. in ravine, 10 ft. deep.
Ascend S. slope of mountain.
- 80.00 Set sandstone, 24x12x12 ins., 18 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked with 5 notches on the S. and 2 notches on the E. edges; from which,
- A fir, 50 ins. diam., bears N.20*E., 29 lks. dist., marked T 25 S R 9 W S 2 B T.
- A fir, 40 ins. diam., bears S.50 $\frac{1}{2}$ *E., 26 lks. dist., marked T 25 S R 9 W S 11 B T.
- A fir, 24 ins. diam., bears S.69 $\frac{1}{2}$ *W., 37 lks. dist., marked T 25 S R 9 W S 10 B T.
- A fir, 20 ins. diam., bears N.5*W., 13 lks. dist., marked T 25 S R 9 W S 3 B T.
- Land, level and mountainous.
Soil, sandy loam and gravelly, 1st. and 3rd. rate.
Timber, fir, hemlock and cedar.
Undergrowth, sallal, huckleberry and vine maple.
Mountainous and heavily timbered lands. 80.00 chs.

N.89*57'E. on a random line bet. secs. 2 and 11.