

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 9 W., W. M.,

CHAINS

79.90

The cor. of secs. 2, 3, 10 and 11.

Land, rolling and mountainous.

Soil, sandy loam and gravelly 2nd. and 3rd. rate.

Timber, fir and hemlock.

Undergrowth, sallow, huckleberry and vine maple.

Mountainous and heavily timbered lands, 79.90 chs.

October 24, 1902

15.75

N.0°02'W. on a true line bet. secs. 2 and 3.

Ascend through heavy timber and scattering undergrowth.

Summit of divide bet. Umpqua and Coos Rivers, 1600 ft.

above Bottom Creek, bears N.60°W. and S.60°E.

Descend over ridges and ravines on N. slope of mountain.

40.00

Set a sandstone, 18x12x4 ins., 12 ins. in the ground,

for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the W. face; from which,

A fir, 10 ins. diam., bears N.31°E. 81 lks. dist.,

marked $\frac{1}{4}$ S 2 B T.A fir, 12 ins. diam., bears S.39 $\frac{1}{2}$ °W. 58 lks. dist.,marked $\frac{1}{4}$ S 3 B T.

59.00

Spring branch, 3 lks. wide. course N.70°E., in ravine,

300 ft. deep.

64.25

Ridge point, 300 ft. high, bears NE. and SW.

Descend over ridges and ravines.

75.20

Intersect the S. Bdy. of T. 24 S., R. 9 W., 23.50 Chs.

W. of the cor. of secs 34 and 35, which is a post,

5 ins. sq., 1 ft. above ground, marked and witnessed

as described by the surveyor general. I destroy all

marks on old cor., pertaining to the survey S. and

75.20

At point of intersection,

Set a basalt stone, 18x12x5 ins., 12 ins. in the ground,

for closing cor. of secs. 2 and 3, marked C C on the

S. face; with 2 grooves on E. and 4 grooves on W. faces;

from which,

A fir, 20 ins. diam., bears S.21°E., 70 lks. dist.,

marked T 25 S R 9 W S 2 B T.