

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 9 W., W. M.,

CHAINS	
	N.0*02'W. bet. secs. 21 and 22.
	Descend through heavy timber and dense undergrowth.
8.00	Ravine, 100 ft. deep, course N.60*E.
	Ascend SE. slope of mountain.
40.00	Set a hemlock post, 4 ins. sq., 3 ft. long 24 ins. in
	the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S. 21 on the W.
	and S. 22 on the E. faces; from which,
	A fir, 20 ins. diam., bears S.21*E., 51 lks. dist.,
	marked $\frac{1}{4}$ S B T.
	A hemlock, 10 ins. diam., bears N.10*W., 31 lks.
	dist., marked $\frac{1}{4}$ S B T.
59.50	Summit of divide bet. Fall Creek and Bottom Creek, 1300
	ft. above Bottom Creek, bears N.30*E. and S.30*W.
	Descend steep NW. slope into Fall Creek.
80.00	Set a basalt stone, 15x10x8 ins., 10 ins. in the ground,
	for cor. of secs. 15, 16, 21 and 22, marked with 3
	notches on S. and E. edges; from which,
	A fir, 12 ins. diam., bears N.33 $\frac{1}{2}$ -E., 18 lks., dist.
	marked T 25 S R 9 W S 15 B T.
	A fir, 10 ins. diam., bears S.53 $\frac{1}{2}$ *E., 31 lks. dist.
	marked T 25 S R 9 W S 22 B T.
	A hemlock, 14 ins. diam., bears S.83*W., 74 lks.
	dist., marked T 25 S R 9 W S 21 B T.
	A fir, 20 ins. diam., bears N. 63*W., 81 lks. dist.
	marked T 25 S R 9 W S 16 B T.
	Land, mountainous.
	Soil, gravelly; 3rd. rate.
	Timber, fir, hemlock and maple.
	Undergrowth, laurel, sallal, huckleberry and vine maple.
	Mountains and heavily timbered land, 80.00 chs.
	S.89*51'E. on a random line bet. secs. 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect N. and S. line 37 lks. S. of the cor. of secs.
	14, 15, 22 and 23.