

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 25 S., R. 9 W. W. M.,

CHAINS

Undergrowth, laurel, vine maple, huckleberry and sallow.
Mountainous and heavily timbered lands. 80.00 chs.

N.0°02'W. on a true line secs. 3 and 4.

Descend along steep E. slope of Millaconia Divide,
through heavy timber and undergrowth.

4.50 Spring branch, 4 lks. wide, in ravine, 200 ft. deep,
course N.60°E.

9.75 Ridge point, 250 ft. high, descends toward the NE.
Over small ravines and ridges.

24.00 Ascend S. slope of Millaconia Divide.

31.25 Millaconia Divide, 1000 ft. above Fall Creek, bears E.
and W.

Descend steep N. slope.

40.00 Set a sandstone 15x10x4 ins, 10 ins. in the ground for $\frac{1}{4}$
sec. cor. marked $\frac{1}{4}$ on W. face; from which,
A fir, 10 ins. diam., bears N.15°W., 103 lks, dist.
marked $\frac{1}{4}$ sec. 3 B T.
A cedar, 12 ins diam. bears S.20 $\frac{1}{2}$ °W., 30 lks. dist.,
marked $\frac{1}{4}$ S 4 B T.

75.44 Intersect S. Bdy. of T. 24 S., R. 9 W., 23.71 chs. W.
of the cor. of sec. 33 and 34 which is a post, 5 ins.
sq., 1 ft. above ground, marked and witnessed as
described by the surveyor general.

I destroy all marks on old cor. pertaining to the survey S.

75.44 ~~S.~~ And at point of intersection.

Set a hemlock post, 4 ins. sq., 3 ft. long 24 ins.
in the ground for closing corner of secs. 3 and 4,
marked C. C. T. 25 S., R. 9 W. on the S., S. 3 on the
E., and S. 4 on the W. faces; with 3 grooves on the E.
and W. faces; from which;

A fir, 20 ins. diam., bears S.63°E., 28 lks. dist.,
marked T 25 S R 9 W S 3 B T.

A hemlock, 20 ins. diam., bears S.15 $\frac{1}{2}$ °W. 53 lks.
dist., marked T 25 S R 9 W S 4 B T.