

East Boundary of T. 26 S., R. 2 W., W. M. as surveyed by  
John A. McQuinn, Deputy Surveyor, under contract #466  
dated April 5, 1883.

CHAINS	
	<p>From the corner to Tps. 26 &amp; 27 S., Ranges 1 &amp; 2 W, which is a chinquapin post 4 ins. sq., firmly set in the ground marked T 26 S S 31 on NE., R 1 W S 6 on SE., T 27 S S 1 on SW., R 2 W S 36 on NW faces with 6 notches on N, E, S &amp; W edges, from which</p> <p>A laurel, 7 ins. diam., bears N.45*E., 28 lks. dist., marked T 26 S R 1 W S 31 B T.</p> <p>A fir, 6 ins. diam., bears S.60*E., 31 lks. dist., marked T 27 S R 1 W S 6 B T.</p> <p>A fir, 40 ins. diam., bears S.74*W., 25 lks. dist., marked T 27 S R 2 W S 1 B T.</p> <p>A fir, 24 ins. diam., bears N.3*W., 23 lks. dist., marked T 26 S R 2 W S 36 B T.</p> <p>I run, North between secs. 31 &amp; 36.</p> <p style="text-align: right;">Va. 19<math>\frac{1}{2}</math>* East.</p> <p>Through heavy timber.</p>
5.80	A fir, 30 ins. diam.
38.10	A brook, 2 lks. wide, course N.40*W.
40.00	<p>Set cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for <math>\frac{1}{4}</math> sec, corner marked <math>\frac{1}{4}</math> S on W face, from which</p> <p>A fir, 6 ins. diam., bears N.10*E., 33 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p> <p>A fir, 8 ins. diam., bears S.34*W., 12 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p>
49.30	A stream, 10 lks. wide, runs W.
60.35	A fir, 36 ins. diam.
80.00	<p>On top of rocky ridge.</p> <p>Set a cedar post 4 ft. long, 4 ins. sq., 24 ins. in the ground for corner to secs. 25, 30, 31 and 36 marked T 26 S S 30 on NE., R 1 W S 31 on SE., R 2 W S 36 on SW and S 25 on NW faces with 5 notches on N and 1</p>