

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 26 S., R's. 1 E & 1 W.

CHAINS

A hemlock, 10 ins. diam., bears S.61*W., 20 lks. dist.,
marked T 26 S R 1 W S 25 B T.

A yew, 5 ins. diam., bears N.71*W., 20 lks. dist.,
marked T 26 S R 1 W S 24 B T.

Land mountainous.

Soil loam and stony, 3rd and 4th rate.

Timber fir, hemlock and yew; undergrowth rhododendron, yew,
hemlock and vine maple.

July 19, 1910.

At the cor. of secs. 19, 24, 25 and 30.

Thence I run

North between secs. 19 and 24.

Over mountainous land, heavily timbered and covered with
dense undergrowth.

Along W slope.

17.75 Creek, 2 lks. wide, course NW.

22.70 Creek, 2 lks. wide, course NW.

27.90 Bluff 20 ft. high.

Descend into canyon.

28.60 Ravine, course W.

Along W slope.

Difference between measurements of 40.00 chs. by two sets
of chainmen is 18 lks., position of middle point

By 1st set, 39.91 chs.

By 2nd set, 40.09 chs., the mean of which is

40.00 Point for $\frac{1}{4}$ sec. cor. falls on a basalt rock in place
5 x 10 x 8 ins. above ground on which I cut a cross(x)
at exact cor. point, and mark $\frac{1}{4}$ W of cross, from which

The perpendicular face of a basalt rock, 5 ft.

high bears S.13 $\frac{1}{2}$ *E., 8 lks. dist., marked with a

cross (x) at exact bearing point B O $\frac{1}{4}$ ^S 19.

A madrone, 5 ins. diam., bears S.57*W., 46 lks.

dist., marked $\frac{1}{4}$ S 24 B T.